





**Model Number: A100XXX**

**Intech microwaves s.r.l.**

Sede Legale e Operativa: Via Giacomo Peroni 400, 00131 Roma (RM) – Italy  
Cap. Soc. € 80.000,00 – P.IVA 12934711008 – REA RM1411466  
Tel: +39 06 4568 3104 - Email : info@intech-mw.com PEC: intech.microwaves@pec.it

## 2Kw X Band Solid State Transmitter

X-Band Solid State Transmitter using GaN Technology



### Features

- 2 Kw Peak Output Power
- Typical frequency range of 8.5 to 9.5 GHz
- Efficiencies as high as 20%
- Up to 110  $\mu$ sec pulse width, 15% duty cycle
- Targeted for TWT Amplifier Replacement
- Military and Commercial Radar Applications

IMW Model A100XXX is a 2 Kw peak output power, solid state amplifier designed as a replacement for traveling wave tube modules over the 8.5 to 9.2 GHz frequency range. Operating by a +50VDC supply, the Model A100XXX has 53 dB minimum gain with performance up to 110  $\mu$ sec pulse widths at 15% duty cycle. Amplitude droop across a pulse of this duration is less than 1 dB. Phase distortion is minimized by gating the discrete power supply OFF during pulsed RF operation. Additional advantages of the GaN power module over a traveling wave tube counterpart include increased MTBF, soft fail vs. catastrophic fail, and lower long term replacement/repair cost. An integrated controller provides customer interface and fault monitoring options.

### Technical Specifications @ 25°C <sup>(1)</sup>

Parameter	Specification
Frequency	8.5÷9.5 GHz
Output Power	+63 dBm Peak (min)
Input Power	+10 to +13 dBm
RF Pulse Width	1 to 110 $\mu$ sec
Duty Cycle	15% (max)
Rise / Fall Time	100 nsec (max)
Efficiency <sup>(2)</sup>	20% (min)
P <sub>OUT</sub> On/Off Ratio	80 dB (min) @ 1.5 Kw
2 <sup>nd</sup> Harmonic	-40 dBc (max) @ 1.5 Kw
3 <sup>rd</sup> Harmonic	-45 dBc (max) @ 1.5 Kw
Spurious (non-harmonic)	-70 dBc (max) @ 1.5 Kw
Noise Power Density <sup>(3)</sup>	-45 dBm/MHz (max)
Input / Output Impedance	50 $\Omega$ (nominal)
Input / Output VSWR	1.5 :1
DC Prime Power <sup>(4)</sup>	+50 VDC

### Mechanical Specifications

Parameter	Specification
Case Dimensions	450mm(L) x 308mm (W)x283mm (H)
Material	Aluminum Alloy
Finish	TIN Plate
Connectors	
RF Input	SMA Female
RF Output	Waveguide
DC Power& Control Interface	Micro D-Subminiature 790-026PH-29P7MP
Weight	30 Kg (max)
Grounding	Chassis

## Model Number: A100XXX

### Environmental Specifications

Ambient Operating Temperature	-40°C to +70°C	—
Absolute Max Baseplate Temperature	+90°C	—
Storage Temperature	-55°C to +100°C	—
Cooling	Adequate Heat Sink Required	Conduction
Relative Humidity	0 to 95%	Non-condensing

### Miscellaneous

Control / Interface Signals	Standby/Operate, Pre-trigger, Remote On/Off, Synchronization	TTL Logic
Maximum Load VSWR	Open / Short (All Phase Angles)	No Damage
MTBF	21,500 hrs. @ +50°C Baseplate Temperature	MIL-HDBK-217

### Notes

1. Specification ratings are based on measurements in a 50 ohm system.
2. Total efficiency of +50 VDC power supply integrated with solid state amplifier.
3. Measured at the RF output with the RF input terminated into a 50 ohm load.
4. Alternate DC power supply voltages available as a custom solution.